


## Inline connector - IB IL SCN-PWR IN - 2727462

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Connector, for Inline power and segment terminal blocks



### Key commercial data

Packing unit	1 pc
Minimum order quantity	10 pc
GTIN	 4 017918 162900
Weight per Piece (excluding packing)	15.7 GRM
Custom tariff number	85366990
Country of origin	Germany

### Technical data

#### Dimensions

Height	111.2 mm
Depth	41 mm
Width	12.2 mm

### Classifications

#### eCl@ss

eCl@ss 4.0	27250281
eCl@ss 4.1	27250281
eCl@ss 5.0	27259205
eCl@ss 5.1	27242692
eCl@ss 6.0	27242692
eCl@ss 7.0	27242692
eCl@ss 8.0	27242692

# Inline connector - IB IL SCN-PWR IN - 2727462

## Classifications

### ETIM

ETIM 2.0	EC000313
ETIM 3.0	EC000313
ETIM 4.0	EC002584
ETIM 5.0	EC002584

### UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	39121311
UNSPSC 12.01	39121311
UNSPSC 13.2	39121311

## Approvals

### Approvals

---

#### Approvals

UL Recognized / cUL Recognized / GOST / cULus Recognized

---


#### Ex Approvals

---

#### Approvals submitted


---

## Approval details


UL Recognized 	
mm <sup>2</sup> /AWG/kcmil	26-16
Nominal current I <sub>N</sub>	10 A
Nominal voltage U <sub>N</sub>	24 V

## Inline connector - IB IL SCN-PWR IN - 2727462

### Approvals

cUL Recognized 	
mm <sup>2</sup> /AWG/kcmil	26-16
Nominal current I <sub>N</sub>	10 A
Nominal voltage U <sub>N</sub>	24 V

GOST 	
--	--

cULus Recognized 	
--	--